

Report Documentation Page				Form Approved OMB No. 0704-0188	
Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.					
1. REPORT DATE 30 SEP 1997		2. REPORT TYPE		3. DATES COVERED 00-00-1997 to 00-00-1997	
4. TITLE AND SUBTITLE Acoustic Imaging of Shallow Water Sediments				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) University of Washington, Applied Physics Laboratory, 1013 N.E. 40th Street, Seattle, WA, 98105				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited					
13. SUPPLEMENTARY NOTES					
14. ABSTRACT					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT Same as Report (SAR)	18. NUMBER OF PAGES 2	19a. NAME OF RESPONSIBLE PERSON
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified			

ACOUSTIC IMAGING OF SHALLOW WATER SEDIMENTS

Dajun Tang

Applied Physics Laboratory, University of Washington

1013 NE 40th Street, Seattle, WA 98105-6698

phone: (206) 543-1290 fax: (206)543-6785 email: djtang@apl.washington.edu

Award # N00014-97-1-0268

Thomas A. Austin and Dezhong Chu

Woods Hole Oceanographic Institution

Woods Hole, MA 02543

phone: (508) 289-2894 fax: (508) 289-2194 email: taustin@whoi.edu

Award # N00014-95-1-0408

LONG-TERM GOAL

Measuring, imaging, and modeling centimeter-scale, three-dimensional, in situ sediment volume inhomogeneities using acoustic tomography.

SCIENTIFIC OBJECTIVES

Sediment volume inhomogeneity on the centimeter scale has a major impact on the design and application of high-frequency sonars, especially when operated in shallow waters. Yet there is little information available on such inhomogeneities due to limitations on measurement techniques. We are developing an in situ probe system using acoustic tomography to image shallow water sediments to obtain sound speed and attenuation coefficient over space.

APPROACH

The in-situ sediment acoustic imaging system consists of an array of needle-like probes which may be pressed into the sediment, where each probe is a line array of acoustic transducers. The current system consists of three identical probes attached to a sturdy frame. Two probes are oriented vertically and pressed into the sediment about 1 meter apart, and the third is oriented horizontally, just above the seafloor, between the two vertical probes. Each probe contains 20 acoustic transducers, arranged as a line array with 5 cm spacing. Each transducer in every probe is capable of both transmit and receive. The transducers used are free flooded cylinders, with a resonant frequency of 100 kHz with approximately 40 kHz bandwidth. All possible raypath combinations between the probes are sequentially interrogated. The objective is to accurately estimate the travel time and amplitude from transmit to receive on each ray path.

WORK COMPLETED

Two data sets were processed. One is from a laboratory experiment and the other is from a field experiment. The tank experiment was conducted to evaluate the performance of

the data acquisition system and inversion algorithms. During the tank experiment, a polyurathane (EN22) block of 14.1 cm in diameter and 7.5 in height was located near the center of the tomographic frame. The sound speed in the polyurathane block is 1816 m/s. The sound speed in water is 1507 m/s at 17 degrees C. The field experiment was conducted near Woods Hole, MA, in November 1996. The sediment is made of soft organic mud. A total of 1200 arrival times were obtained from 1200 transmit/receive combinations via post-processing program. The arrival times were picked in an interactive mode. There were 30 pings acquired for each ray path and the signals averaged. Typical standard deviations of the arrival time were less than 50 ns.

RESULTS

Sound speed inversion from the tank experimental data shows that the polyurathane block is clearly identifiable and its position was correctly located by the inversion algorithm. Spreading in sound speed due to diffraction is observed. Sound speed image of the field data shows a 10% variation in a 1 meter by 1 meter region. Attenuation coefficient inversion from the mud data reveals that the attenuation coefficient varies from 10 dB/m to 65 dB/m at 100 kHz. Comparison of the sound speed image with the attenuation coefficient image shows that some regions with higher sound speed correspond to lower attenuation coefficient while some other regions correspond to higher attenuation coefficient. It is found that gas bubbles might be present and multiple scattering effects could be important. Future modeling work will address this issue.

IMPACT/APPLICATION

Since this probe system can measure in situ sound speed and attenuation coefficient of sediments over two-dimensions, its advantage over coring is obvious. In addition to applications to high-frequency bottom acoustics, it can provide much needed information to the marine geology and biology communities.

RELATED PROJECTS

In the ONR-DRI on High-Frequency Sound Interaction in Ocean Sediments over the next five years, this system will be improved and updated to provide sediment volume inhomogeneity data in sandy as well as muddy bottoms.